# **TCOAST**<sup>®</sup>COAST<sup>™</sup>

## **Automotive U-Joints**

### Coverage

Coast to Coast covers the most popular applications ranging from light duty domestic and import car applications up to heavy duty truck applications.

### Quality


Coast to Coast U-Joints are designed for optimal life and precise fit for every application. All products are manufactured in ISO-9000 or TS-16949 certified factories ensuring the highest quality is built into every U-Joint.

### Styles

Coast to Coast Universal Joints are available in a wide range of cap styles and combinations including; internal snap ring, external snap ring, full round, 1/2 round and wing-style.

- Journal Crosses are forged from a high quality steel which are case hardened to achieve a surface hardness of 58-64 HRC while maintaining a ductile core hardness of 25-48 HRC providing a hard roller surface for strength and long life without brittleness.
- 2. Trunnions are Coast to Coast ground providing a smooth surface that reduces wear.
- 3. Rollers are heat treated to a hardness of 60-66 HRC then Coast to Coast ground and sized to exact dimensions for proper roller clearance and maximum load capacity.
- Universal Joints are pre-lubricated at the factory with EP (Extreme Pressure) NLGI grade 2 grease with an operating range of -10°F to 325°F.
- 5. Dust Caps provide an additional barrier to help exclude contaminates.
- 6. Bearing Cups are case hardened to a hardness of 58-64 HRC and Coast to Coast ground for a precise yoke fit.
- Internal Seal Bearing Cups contain a triple lip seal construction for maximum grease retention and contaminate exclusion.
- 8. Zerk Fittings are located for easy access to allow re-lubrication during preventive maintenance.

### All Universal Joints are supplied with the necessary installation hardware.



Coast to Coast Toll Free: (800) 627-0700 • Toll Free Fax: (800) 627-9401 • www.northcoastbearings.com

COAST COAST

# **TCOAST**<sup>©</sup>**COAST**<sup>™</sup>

6

COASTECOAST

## **Heavy Duty U-Joints**

#### Coverage

Coast to Coast provides coverage on U-Joints for all of the popular medium and heavy duty applications ranging from the 1310 to 1880 series of drivelines including the new long life high torque capacity drivelines.

### Quality

Coast to Coast U-Joints are designed for optimal life and precise fit for every application. All products are manufactured in ISO-9000 or TS-16949 certified factories ensuring the highest quality is built into every U-Joint.

#### Styles

Coast to Coast Universal Joints are available in a wide range of cap styles and combinations including; internal snap ring, external snap ring, full round, 1/2 round and wing-style.

- Journal Crosses are forged from a high quality steel which are case hardened to achieve a surface hardness of 58-64 HRC while maintaining a ductile core hardness of 25-48 HRC providing a hard roller surface for strength and long life without brittleness.
- 2. Trunnions are Coast to Coast ground providing a smooth surface that reduces wear.
- 3. Rollers are heat treated to a hardness of 60-66 HRC then Coast to Coast ground and sized to exact dimensions for proper roller clearance and maximum load capacity.
- Universal Joints are pre-lubricated at the factory with EP (Extreme Pressure) NLGI grade 2 grease with an operating range of -10°F to 325°F.
- 5. Dust Caps provide an additional barrier to help exclude contaminates.
- Bearing Cups are case hardened to a hardness of 58-64 HRC and Coast to Coast ground for a precise yoke fit.
- 7. Internal Seal Bearing Cups contain a triple lip seal construction for maximum grease retention and contaminate exclusion.
- 8. Zerk Fittings are located for easy access to allow re-lubrication during preventive maintenance.

### All Universal Joints are supplied with the necessary installation hardware.



Coast to Coast Toll Free: (800) 627-0700 • Toll Free Fax: (800) 627-9401 • www.northcoastbearings.com